

GOODYEAR ECODRIVE 5W-30

Passenger Car Motor Oil (PCMO)

EN Synthetic top quality engine oil suitable for latest generation diesel engines equipped with exhaust after-treatment devices like DPF. Developed especially for diesel engines where Renault specification RN0720 is required. Modern low ash technology protects against ash in the filter and improves their mode of action and service life.

LT Sintetinė aukščiausios kokybės variklinė alyva, tinkanti naujausios kartos dyzeliniams varikliams su papildomo išmetamųjų dujų apdorojimo įrenginiais, tokiais kaip DPF. Sukurta specialiai dyzeliniams varikliams, kuriems reikalinga Renault specifikacija RN0720. Šiuolaikinė mažai pelenų technologija apsaugo nuo pelenų filtrė ir pagerina jų veikimo būdą bei tarnavimo laiką.

LV Sintētiska augstākās kvalitātes motoreļļa piemērota jaunākās paaudzes dīzeļdzinējiem, kas aprīkoti ar izplūdes gāzu pēcapstrādes ierīcēm, tādām kā DPF. Izstrādāta speciāli dīzeļdzinējiem, kur nepieciešama Renault specifikācija RN0720. Modernā zema pelnu līmeņa tehnoloģija aizsargā pret pelniem filtrā, uzlabo tā darbību un pagarina kalpošanas laiku.

EE Sünteetiline tippkvaliteediga mootoriõli, mis sobib uusima põlvkonna diiselmootoritele, mis on varustatud heitgaaside järeltöötlusseadmetega, nagu DPF. Välja töötatud spetsiaalselt diiselmootoritele, kus nõutakse Renault spetsifikatsiooni RN0720. Kaasaegne vähese tuhasisaldusega tehnoloogia kaitseb filtris oleva tuha eest ning parandab nende toimimisviisi ja kasutusiga.

SAE 5W-30

ACEA C4

MB 226.51/229.31

RN0720

Typical data	Method	Value
Density at 15°C, g/cm ³	ASTM D 1298	0,850
Viscosity at 100°C, mm ² /s (cSt)	ASTM D 445	11,9
Viscosity index (VI)	ASTM D 2270	173
Flash point COC, °C	ASTM D 92	240
Pour point, °C	ASTM D 97	- 40
T.B.N. (Total Base Number), mg KOH/g	ASTM D 2896	8,0

The average values are given for information, values may vary within the official limits. Safety data sheet available on request.

Packing			
1L	4L	5L	208L