

GOODYEAR POWERAX 75W-90

Multi Purpose Gear Oil + Limited Slip Differential

EN Synthetic multi-grade transmission oil containing special limited slip additive. Suitable for passenger car, off-road and commercial vehicle transmission units with and without self-locking differentials in accordance with the vehicle manufacturer's instructions. Provide outstanding thermal stability, excellent corrosion protection.

LT Sintetinė daugiavfunkcė transmisijos alyva su specialiu riboto slydimo priedu. Tinkama lengvųjų automobilių, visureigių ir komercinių transporto priemonių pavarų dėžėms su riboto slydimo diferencialais ir be jų pagal transporto priemonės gamintojo instrukcijas. Suteikia išskirtinį temperatūros stabilumą, puikią apsaugą nuo korozijos.

LV Sintētiska vissezonu transmisijas eļļa, kas satur īpašu ierobežotas slidēšanas piedevu. Piemērota vieglo automašīnu, apvidus auto un komerctransporta transmisijas agregātiem ar ierobežotas slīdes diferenciāļiem un bez tiem saskaņā ar transportlīdzekļa ražotāja norādījumiem. Nodrošina izcilu termisko stabilitāti, lielisku aizsardzību pret koroziju.

EE Sünteetiline universaalne transmissiooniõli mis sisaldab spetsiaalset piiratud libisemisliisandit. Sobib piiratud libisemisega diferentsiaalidega ja ilma nendeta sõiduautode, maasturite ja tarbesõidukite käigukastidele vastavalt sõidukitootja juhiste kohaselt. Tagab silmapaistva termilise stabiilsuse ja suurepärase korrosioonikaitse.

SAE 75W-90
API GL-4/GL-5/LS

ZF TE-ML 12E/16D/19B/21A
BMW Hypoid Axle Oil G1

MAN 342 M1/M2
FIAT 9.55550-DA4/9

DEXRON LS GEAR
VW G50/51/052196

Typical data	Method	Value
Density at 15°C, g/cm ³	ASTM D 1298	0,87
Viscosity at 100°C, mm ² /s (cSt)	ASTM D 445	14,7
Viscosity index (VI)	ASTM D 2270	173
Flash point COC, °C	ASTM D 92	205
Pour point, °C	ASTM D 97	- 38

The average values are given for information, values may vary within the official limits. Safety data sheet available on request.

Packing			
1L	4L	20L	208L